

Denne artikel er publiceret i det elektroniske tidsskrift

**Artikler fra Trafikdage på Aalborg Universitet**

(Proceedings from the Annual Transport Conference  
at Aalborg University)

ISSN 1603-9696

[www.trafikdage.dk/artikelarkiv](http://www.trafikdage.dk/artikelarkiv)



# The emission consequences of using biodiesel and bio ethanol as a fuel road transport

Morten Winther<sup>1</sup> ([mwi@dmu.dk](mailto:mwi@dmu.dk)), Flemming Møller<sup>1</sup>, Marlene S. Plejdrup<sup>1</sup>, Thomas C. Jensen<sup>2</sup>

<sup>1</sup>DCE – Center for Environment and Energy, Aarhus University, Frederiksborgvej 399, 4000  
Roskilde, Denmark

<sup>2</sup>Technical University of Denmark, DTU Transport, DK-2800 Lyngby, Denmark

---

## Abstract

This article explains the emission consequences of using biodiesel and bio ethanol as a fuel for road transport in Denmark calculated in the REBEca project. For the years 2004, 2010, 2015, 2020, 2025 and 2030, two fossil fuel baseline scenarios (FS) are considered characterised by different traffic growth rates. For each FS, two biofuel scenarios (BS1, BS2) are considered with a 5.75 % biodiesel/bio ethanol share in 2010 as a common starting point. From 2010, linear growths are assumed for BS1 (10 % in 2020) and BS2 (25 % in 2030).

The emissions presented in this study are vehicle based; a separate W-t-W assessment of the total emission consequences of producing and using biofuels has been conducted in a different part of REBEca. The maximum CO<sub>2</sub> emission difference between FS and BS2 becomes 26 % in 2030. The NO<sub>x</sub> and VOC emission variations between FS and both biofuel scenarios are 3 % or less. For CO and TSP the largest emission differences, 5 % and -12 %, respectively, occur between the FS and BS2 scenarios in 2030. The biofuel emission impacts are insignificant for NO<sub>x</sub>, VOC, CO and TSP compared to the generally large emission reductions predicted in all scenarios driven by the gradual strengthened emission standards for new vehicles, by far outweighing the emission influence from biofuels and traffic growth.

The emission estimates for NO<sub>x</sub>, VOC, CO and TSP presented in this study are less certain than for CO<sub>2</sub> due to the relatively scarce biofuel emission data implemented in the calculations. As a consequence, the obtained emission results must be assessed with care. Bearing in mind these uncertainties, the calculation approach for emissions from biofuel usage presented in this study can be used as a tool to carry out sensitivity analysis, environmental impact assessment studies, or for research purposes as such.

---

## 1. Introduction

The introduction of biofuels is seen as a very important measure to reduce the emissions of greenhouse gases from road transport; first of all CO<sub>2</sub> emissions because biofuels are regarded as CO<sub>2</sub> neutral fuels (EU Directive 2009/28/EC). The CO<sub>2</sub> emission consequences of introducing biofuels depend on the amount of transport. This, together with fuel effectiveness of vehicles, total vehicle fleet and composition with regard to age and size and decisions about the biofuel share of fuel consumption determines the CO<sub>2</sub> reduction potential.

In Denmark the biofuel target for the transport sector in Denmark is 5.75 % in 2010 (phased in until 2012). In 2020, 10 % of the energy consumption in the transport sector is to be covered by renewable energy, including biofuel. This is the background for the multi-disciplinary integrated impact assessment project 'Renewable Energy in the transport sector using Biofuels as an Energy Carrier' (REBECa), which was finalised recently. The aims of REBECa was to assess the impact on emissions, air quality and human health as well as resource and land-use change, and to consider economic and sociological aspects of the future use of biodiesel and bio ethanol in Danish road transport. The project period was 2007–2010.

An important task in REBECa was to estimate the fuel consumption and emissions for two fossil fuel based baseline scenarios (FS) for Danish road transport, characterised by different traffic growth rates. For each of the baseline scenarios, two biofuel scenarios (BS1 and BS2) were considered with different penetration rates of biodiesel and bioethanol. Fuel consumption and emission calculations of CO<sub>2</sub>, SO<sub>2</sub>, NO<sub>x</sub>, TSP, CO and VOC were made for the baseline year 2004, and the scenario years 2010, 2015, 2020, 2025 and 2030.

The purpose of the present paper is to describe the emission inventory and the calculated results. A short methodology description will be given in terms of fleet specific mileage data, baseline emission factors, biofuel emission difference functions and calculation method. In the results part, baseline emission results will be given in time-series. Further, comparisons will be made for the baseline and biofuel scenarios in the discrete scenario years in order to assess the emission impact of biofuel usage. Selected emission results are also displayed on GIS maps for Denmark.

Increased consumption of biofuels also has indirect emission consequences related to the full chain of production, distribution and combustion of biofuels. The indirect consequences of re-allocating society's scarce resources are best analysed within an integrated Life Cycle and Well-to-Wheel (LCA/W-t-W) framework (e.g. Menichetti & Otto, 2008; UNEP, 2009; Hoefnagels et al., 2010; Londo et al., 2010; Whitaker et al., 2010). In another part of REBECa, a W-t-W assessment of the total emission consequences of producing and using biofuels is made, where it is combined with a welfare economic cost benefit analysis to assess the consequences for society's welfare of the different biofuel scenarios (Slentø et al., 2010). The main conclusions from this study with regard to CO<sub>2</sub> emissions are presented in the discussion part of this paper.

## 2. Activity data

### 2.1 Total mileage data

The mileage forecast used in the REBECa project is prepared by DTU Transport in Denmark. The mileage forecast which is based on an oil price of \$65 pr barrel of oil (Fosgerau et al., 2007), is also used as an input to the Danish Infrastructure Commission (2008). Due to the very high oil prices in 2008 and the latest estimate of \$100-120 pr barrel for the future oil price from IEA, an alternative mileage scenario for the REBECa project is also calculated by DTU Transport, based on an oil price of 100\$ pr barrel. A documentation of the mileage forecast is given by Jensen and Winther (2009).

In order to make sufficiently detailed fuel consumption and emission estimates in REBECa, the DTU mileage figures must be grouped into vehicles with the same average fuel consumption and emission behaviour; the so-called layers. An internal model developed by DCE (Winther, 2008; Nielsen et al., 2009) uses a layer structure and calculation methodology similar to the model structure of the European emission calculation model COPERT. The layer splits are made according to fuel type, engine size/weight class and EU emission legislation levels. Figure 1 shows the layer split of DTU mileage forecast, aggregated from engine size (cars) and weight class (trucks) though.




Figure 1 - Layer distribution of total mileage pr vehicle type in 2004-2030

## 2.2 Energy input data

BS 1 assumes an energy share of biodiesel and bio ethanol of 5.75 % in 2010, followed by a linear growth to 10 % in 2020, and with constant levels in the following years. In BS2 the biofuel share is also 5.75 % in 2010 and subsequently the biofuel share grows linearly to 25 % in 2030. For biodiesel full miscibility is assumed, whereas for bioethanol the definition is to use a 5 % mix by volume of bioethanol in the standard gasoline fuel (E5), and let the surplus of ethanol available be used by FFV's (Flexible Fuel Vehicles) running on E85 (85 vol % ethanol + 15 % gasoline).

By taking into account the differences in fuel density,  $\rho$ , and lower heating values (LHV) between fossil based fuels and biofuels<sup>1</sup>, by simple transformation (Winther, 2010) the volume based biofuel percentage, B%, and the resulting LHV's can be derived for the 2010-2030 scenario period for diesel-biodiesel and separately for E5/E85 (Figure 2).

<sup>1</sup> LHV (diesel<sup>a</sup>, biodiesel<sup>b</sup>, gasoline<sup>a</sup>, bio ethanol<sup>a</sup>): 42.7, 37.6, 43.8, 26.7 MJ/kg; <sup>a</sup>) DEA (2008), <sup>b</sup>) Teknologirådet (2006)  
P (diesel, biodiesel, gasoline, bio ethanol): 0.84, 0.88, 0.75, 0.79 kg/l; DEA (2008)




Figure 2 - Volume based biofuel % and lower heating values for biodiesel blends and E5/E85 in main scenarios

### 3. Fuel consumption and emission factors

#### 3.1 Baseline fuel consumption and emission factors

For the baseline scenarios, fuel consumption and emission factors used in the calculation model come from the COPERT model version IV (EMEP/EEA, 2009) used for Danish national estimates. Due to the very detailed fleet classification and the further split of mileage into driving situations, the number of emission factors is very big and hence it is not possible to show the emission factors in full details<sup>2</sup>. Figure 3 presents the layer specific NO<sub>x</sub> (except diesel cars) and TSP (except gasoline cars) emission factors for gasoline and diesel cars, trucks and buses, which underpin the emission discussions in Section 6.

<sup>2</sup> The fuel consumption and emission factors depend on vehicle category, fuel type, engine size or weight class, EU emission level and road type. For cars/vans, cold start influence the fuel consumption and CO, VOC, NO<sub>x</sub> and TSP emissions. For gasoline catalyst cars/vans, catalyst wear has an impact on the CO, VOC and NO<sub>x</sub> emissions




Figure 3 - Layer specific NO<sub>x</sub> and TSP emission factors per vehicle category

### 3.2 Fuel consumption and emission factor changes as a function of blend ratio

For Euro 0-III heavy-duty engines the changes in fuel consumption and NO<sub>x</sub>, PM, CO and VOC emissions as a function of B%<sub>v</sub>, is based on the findings from EPA (2002). The data from the latter source is also used for the future Euro VI engine technology, as assumed by Winther (2009). For Euro IV and V engines, the experimental basis behind the curves is measurement results from McCormick et al. (2005). The fuel consumption and the Euro 0-III/Euro IV-V emission curves for NO<sub>x</sub> and PM are shown in Figure 4. For neat biodiesel, the CO[VOC] % emission changes are -48[-67] and -40[-25], for Euro 0-3 and Euro IV-V, respectively.




Figure 4 - Fuel consumption/emission changes (function of B%) for heavy-duty engines and diesel cars/vans

In the case of passenger cars and vans, average emission differences for B10, B20, B30, B50, B70 and B100 are calculated based on the results from four experimental studies (Martini et al. (2007a); Fontaras et al. (2007, 2008); Durbin et al. (2007)), see Winther (2009). The emission differences expressed as linear functions are shown in Figure 4 for NO<sub>x</sub>, CO, VOC and PM. For fuel consumption the relative changes were

not derived explicitly for passenger cars and vans, due to lack of data. For these vehicle types, instead the general relations for heavy-duty vehicles are used. This decision is discussed in Winther (2009).

To characterise the energy consumption and emission factor differences between neat gasoline and E5 and E85, respectively, average differences are calculated by Winther et al. (2012) from eight European studies (E5: Martini et al. (2007b), Delgado (2003), Hull et al. (2005); E85: de Serves et al. (2005), Westerholm et al. (2008), Martini et al. (2009), Pelkmans et al. (2010), AVL MTC (2011)<sup>3</sup>). In the experiments using E85 fuels, the base fuel was E5<sup>4</sup>. However, noting the small average differences between neat gasoline and E5 - and due to lack of experimental data for modern European cars using neat gasoline and E85 - the E5 vs. E85 differences are used in REBECa for the neat gasoline vs. E85 case as well. This decision is discussed in more details by Winther (2012).




Figure 5 - Fuel consumption and emission changes for neat gasoline and E5/E85 for gasoline cars and vans

#### 4. Fuel consumption and emission calculations

For each inventory year and vehicle layer, fuel consumption and emissions are calculated as the product of fuel consumption/emission factors and total mileage (Figure 1). The emissions are calculated as:

$$E_{i,j,y} = emf_{i,j,y} \cdot (100 + k_i(B\%_v)) / 100 \cdot M_{j,y} \quad (1)$$

E = emission (tons), emf = emission factor (g/km),  $k_i$  = emission change function, i = emission component,  $B\%_v$  = vol. based biofuel % (Fig. 2), y = year, j = layer, M = total mileage (mio km; Fig. 2).

The fuel consumption by energy for diesel-biodiesel is calculated as:

$$E_{i,j,y} = fc_{M,B0} \cdot LHV(B\%_v) \cdot (100 + k_{fc}(B\%_v)) / 100 \cdot M_{j,y} \quad (2)$$

E = Energy consumption (GJ),  $fc_M$  = fuel consumption factor (g/km), LHV = lower heating value (MJ/kg; Fig. 2),  $k_{fc}$  = fuel consumption change function (Fig. 4).

The fuel consumption by energy for E5/E85 is calculated as:

$$E_{i,j,y} = fc_{M,E0} \cdot LHV_{E0} \cdot (100 + k_{fc}(E\%)) / 100 \cdot M_{j,y} \quad (3)$$

<sup>3</sup> AVL MTC emission test data for 17 FFV vehicles expanded the emission database after REBECa was finalised

<sup>4</sup> From 2011, E5 is the baseline fuel quality in Denmark.

$E$  = Energy consumption (GJ),  $f_{cM}$  = fuel consumption factor (g/km), LHV = lower heating value (MJ/kg; Fig. 2),  $E\%$  =  $E5/E85$ ,  $k_{fc}$  = energy consumption change function (Fig. 5).

According to the guidelines for United Nations Framework Convention on Climate Change (UNFCCC) and the UNECE Convention on Long Range Transboundary Air Pollutants (CLRTAP) reporting, the biofuel part of the combusted fuel is regarded as CO<sub>2</sub> neutral. By following this definition, the CO<sub>2</sub> emissions are calculated as the product of the energy related emission factor for CO<sub>2</sub> (kg/GJ) and the fossil part of total energy consumption (Eq. 2/3; Fig. 2).

For bioethanol it is assumed that in 2010 FFV's that belong to the most modern Euro layer for gasoline cars (Euro 4) uses the amount of ethanol not being used as E5 blends by gasoline vehicles as such. In 2015 the share of Euro 4 vehicles being FFV's is maintained, hence assuming approximately the same rate of scrapping of vehicles irrespective of technology. Further, the remaining ethanol surplus is assumed to be used by the most modern Euro classes in 2015 (Euro 5 and 6). This step wise ethanol allocation principle is used for the years 2020, 2025 and 2030 also.

## 4. Fuel consumption and emission results

### 5.1 Total fuel consumption and emissions

The calculated totals for fuel consumption, CO<sub>2</sub>, NO<sub>x</sub>, TSP, CO and VOC are shown in Table 1 for the baseline (FS) and biofuel (BS1, BS2) scenarios based on the 65 \$ and 100 \$ mileage forecasts, respectively.

The total mileage increase is higher for the 65 \$ forecast than for the 100 \$ forecast and this is also reflected in the calculated results.

**Table 1 - Fuel consumption and emission results for the baseline and biofuel scenarios calculated in the present study**

| Scenario | Year | Mileage forecast: 65 \$ |                         |             |            |                          | Mileage forecast: 100 \$ |              |                         |             |            |                          |             |
|----------|------|-------------------------|-------------------------|-------------|------------|--------------------------|--------------------------|--------------|-------------------------|-------------|------------|--------------------------|-------------|
|          |      | Energy<br>PJ            | NO <sub>x</sub><br>Tons | VOC<br>Tons | CO<br>Tons | CO <sub>2</sub><br>kTons | TSP<br>Tons              | Energy<br>PJ | NO <sub>x</sub><br>Tons | VOC<br>Tons | CO<br>Tons | CO <sub>2</sub><br>kTons | TSP<br>Tons |
| FS       | 2004 | 164.8                   | 75960                   | 29470       | 200099     | 12114                    | 2854                     | 164.8        | 75960                   | 29470       | 200099     | 12114                    | 2854        |
| FS       | 2010 | 178.8                   | 60389                   | 16824       | 116153     | 13170                    | 2297                     | 161.1        | 56186                   | 15431       | 103520     | 11868                    | 2087        |
| FS       | 2015 | 190.4                   | 44868                   | 10957       | 70500      | 14035                    | 1430                     | 169.0        | 40830                   | 10142       | 63007      | 12460                    | 1279        |
| FS       | 2020 | 204.8                   | 29011                   | 8364        | 48727      | 15101                    | 847                      | 180.0        | 25866                   | 7785        | 43766      | 13268                    | 750         |
| FS       | 2025 | 220.0                   | 18959                   | 7155        | 39462      | 16220                    | 465                      | 191.3        | 16593                   | 6638        | 35341      | 14105                    | 410         |
| FS       | 2030 | 235.5                   | 14197                   | 6566        | 36135      | 17370                    | 304                      | 202.7        | 12244                   | 6046        | 32071      | 14946                    | 267         |
| BS1      | 2010 | 178.5                   | 61301                   | 16408       | 116654     | 12387                    | 2216                     | 160.8        | 57006                   | 15061       | 103923     | 11162                    | 2013        |
| BS1      | 2015 | 189.8                   | 45548                   | 10787       | 70983      | 12889                    | 1361                     | 168.5        | 41446                   | 9991        | 63402      | 11444                    | 1217        |
| BS1      | 2020 | 204.0                   | 29510                   | 8325        | 49353      | 13534                    | 797                      | 179.2        | 26313                   | 7749        | 44293      | 11893                    | 706         |
| BS1      | 2025 | 219.0                   | 19280                   | 7167        | 40147      | 14538                    | 439                      | 190.5        | 16874                   | 6648        | 35925      | 12644                    | 388         |
| BS1      | 2030 | 234.5                   | 14406                   | 6595        | 36855      | 15568                    | 289                      | 201.8        | 12424                   | 6071        | 32688      | 13397                    | 253         |
| BS2      | 2010 | 178.5                   | 61301                   | 16408       | 116654     | 12387                    | 2216                     | 160.8        | 57006                   | 15061       | 103923     | 11162                    | 2013        |
| BS2      | 2015 | 189.6                   | 45699                   | 10795       | 71124      | 12498                    | 1338                     | 168.3        | 41586                   | 9995        | 63517      | 11098                    | 1197        |
| BS2      | 2020 | 203.5                   | 29714                   | 8367        | 49697      | 12694                    | 770                      | 178.8        | 26498                   | 7784        | 44583      | 11156                    | 683         |
| BS2      | 2025 | 218.0                   | 19517                   | 7280        | 40891      | 12831                    | 414                      | 189.6        | 17084                   | 6745        | 36560      | 11161                    | 366         |
| BS2      | 2030 | 233.0                   | 14599                   | 6782        | 38016      | 12884                    | 267                      | 200.5        | 12591                   | 6231        | 33682      | 11091                    | 235         |

In the case of CO<sub>2</sub>, the FS baseline emissions become significantly higher than the emissions estimated for BS1 and BS2, and most markedly for the most ambitious BS2 case. This is clear from the relative emission changes between 2004 and 2030; for FS, BS1 and BS2 (results in brackets) these figures become [43 %, 28 %, 6 %] and [23 %, 10 %, -9 %], for the 65 \$ and 100 \$ mileage forecast, respectively. Of course, this result is due to according to conventional inventory guidelines, biofuels are regarded as CO<sub>2</sub> neutral for exhaust emissions (vehicle based emissions). However, even if the CO<sub>2</sub> consequences of all activities within the entire W-t-W chain from agricultural production to manufacturing, distribution and engine combustion of the biofuel are included, the total CO<sub>2</sub> emissions will in most cases decrease, see (Slentø et al., 2010).

For each mileage case and for each of the remaining emission components/fuel consumption, the calculated changes between 2004 and 2030 become very similar for FS, BS1 and BS2. For FS, the following differences are calculated for fuel consumption, NO<sub>x</sub>, TSP, CO and VOC in the 65 \$[100 \$] mileage case; 43 %[23 %], -81 %[-84 %], -89 %[-91 %], -82 %[-84 %] and -78 %[-79 %]. The percentage differences between FS and the BS1/BS2 scenarios are shown in section 5.3 (Table 6), and more thoroughly discussed in this part of the paper.

## 5.2 Fuel consumption and emissions for the baseline scenarios

For the 65 \$ mileage forecast the calculated results are shown per vehicle category in Figure 6. For the 100 \$ mileage forecast, the emission trends are similar, the total emissions however being somewhat lower due to a smaller traffic growth throughout the forecast period (c.f. Table 1).




Figure 6 - Total energy consumption and emission results per vehicle type for the baseline scenario 2004-2030

In general, the emission development for the different vehicle categories is explained by the development in vehicle mileage and the layer specific emission factors. Significant emission reductions are noted for the combustion related emissions of NO<sub>x</sub>, TSP, CO and VOC. The emission impact from the gradual strengthened emission standards for new sold vehicles is greater than the emission impact from traffic growth during the forecast period.



The fuel consumption and CO<sub>2</sub> emissions increase by 43 % from 2004 to 2030. Cars is the most important source followed by trucks/buses and vans. The emission increase is highest for trucks/buses and vans, 51 % and 48 %, respectively, due to a larger traffic growth for trucks and diesel vans in particular (Figure 1).

For NO<sub>x</sub> and TSP, the total emissions decrease by 81 % and 89 %, respectively, from 2004 to 2030. Trucks and buses as a single group, and cars, are the most important sources of NO<sub>x</sub> and TSP emissions. Trucks and buses have the highest NO<sub>x</sub>[TSP] emissions until 2027[2012], from this year onwards cars becomes the largest emission source. For cars, the NO<sub>x</sub>[TSP] emissions decrease of 72 %[83 %], are somewhat smaller than the total emission decline due to a gradually larger share of diesel cars expected in the future vehicle fleet.


The total CO and VOC emissions decrease are 82 and 78%, respectively, in the same time period. For VOC, the relative emission importance of 2-wheelers becomes large due to less stringent emission legislation standards for these vehicle types compared to the remaining vehicle categories.

The non exhaust emissions from brake, tyre and road wear are shown in Table 2. The non exhaust emissions increases correspond with the increase in traffic. This emission development is in opposition to the exhaust related particulate emissions which are being reduced as a result of the introduction of improved emission reduction technologies. Hence, for the TSP, PM<sub>10</sub> and PM<sub>2.5</sub> size fractions, the non exhaust emission shares of total road transport particulate emissions significantly change from 47 %, 37 % and 24 % in 2004, to 93 %, 89 % and 81 % in 2030.

**Table 2 - Non exhaust emission totals for the 65 \$ and 100\$ mileage forecast**

| Mileage forecast: 65 \$ |             |                          |                           | Mileage forecast: 100 \$ |             |                          |                           |
|-------------------------|-------------|--------------------------|---------------------------|--------------------------|-------------|--------------------------|---------------------------|
| Year                    | TSP<br>Tons | PM <sub>10</sub><br>Tons | PM <sub>2.5</sub><br>Tons | Year                     | TSP<br>Tons | PM <sub>10</sub><br>Tons | PM <sub>2.5</sub><br>Tons |
| 2004                    | 2556        | 1644                     | 895                       | 2004                     | 2556        | 1644                     | 895                       |
| 2010                    | 2836        | 1825                     | 994                       | 2010                     | 2566        | 1651                     | 899                       |
| 2015                    | 3060        | 1969                     | 1072                      | 2015                     | 2726        | 1754                     | 955                       |
| 2020                    | 3312        | 2131                     | 1160                      | 2020                     | 2917        | 1877                     | 1021                      |
| 2025                    | 3575        | 2300                     | 1252                      | 2025                     | 3112        | 2002                     | 1089                      |
| 2030                    | 3846        | 2474                     | 1346                      | 2030                     | 3308        | 2128                     | 1158                      |

The spatial distribution of the road transport NO<sub>x</sub> emissions are shown in Figure 7 for the 65 \$ baseline scenario, as an example. The step wise emission reductions from 2004, 2010, 2020 and 2030 are clearly visible from the maps. The spatially distributed emission results are further used as input for air dispersion modelling purposes, subsequently carried out in REBECa.






Figure 7 - Baseline NO<sub>x</sub> emissions for Danish road transport in 2004, 2010, 2020 and 2030

### 5.3 Fuel consumption and emissions differences between baseline and biofuel scenarios

In relation to the following Figures 8-10, some of the most important fuel consumption and emission differences between the 65 \$ baseline scenario and the most ambitious biofuel scenario, BS2, are explained in the following. The trend and emission difference explanations given for the 65 \$ forecast results, are valid for the 100 \$ forecast also. In the latter case the emission levels are only somewhat lower due to less mileage in the underlying traffic forecast.




Figure 8 - Baseline, BS1 and BS2 energy consumption and CO<sub>2</sub> emission results per fuel type in the scenario years

As shown in Figure 8, the consumption of gasoline decreases until 2020, whereas an increase in the diesel consumption is expected during the entire forecast period, due to the envisaged dieselification of the car fleet in the future. For the individual scenario years small fuel consumption declines (c.f. Table 3 below) are calculated due to the small improvement in thermal efficiency for the engines using biofuel at different blend ratios.

For CO<sub>2</sub> the same trends are visible for the baseline scenario as for fuel consumption. For the biofuel scenarios the growth in CO<sub>2</sub> emissions from diesel vehicles become smaller than the growth in fuel

consumption, and for gasoline vehicles direct emissions decline are noted for BS2 during the forecast period. As mentioned above, the reason is that according to conventional inventory guidelines, biofuels are regarded as CO<sub>2</sub> neutral for exhaust emissions (vehicle based emissions).

For the important NO<sub>x</sub> sources trucks and buses (c.f. Section 5.2), the emissions are shown on Figure 9, for BS2 as totals as well as the absolute changes between BS2 and the baseline scenario. Please note the significant scaling difference for the secondary axis between BS2 totals and BS2/baseline changes; the latter emission changes are small and in relative terms the highest calculated emission penalties never exceed 4.5 % being calculated for 2027.




Figure 9 Layer distributions of NO<sub>x</sub> emissions for trucks and buses for the baseline and BS2 scenarios

From a maximum NO<sub>x</sub> emission difference in 2017 corresponding to a biofuel share of 12.5 % (Figure 2), the emission penalties shown in Figure 9 gradually become smaller as total emissions decrease further until 2030. This decrease in total emissions have a much higher impact on the calculated emission penalties than the increasing emission factor differences between neat diesel and biodiesel (Figure 4), for biofuel shares going up to 25 % in 2030.

From 2012 onwards, the largest part of the extra emissions of NO<sub>x</sub> due to biofuel usage is calculated for Euro V vehicles, which have the highest emission factor changes (Figure 4). As years pass, the emission importance for Euro V vehicles becomes less and less important due to their decreasing mileage (Figure 1). In 2030, the NO<sub>x</sub> emission factor differences become 8 % and 2.6 %, respectively, for Euro V and VI vehicles (Figure 4). However, by the end of the forecast period the latter vehicle group comprise by far most of the mileage being driven with trucks and buses.

From 2012 diesel cars become the largest source of TSP emissions (Figure 6). For this vehicle type, the total emissions are shown in Figure 10 for the baseline scenario and BS2. The expected emission savings gradually increase to 16 % in 2030, as predicted by the emission factor differences between neat diesel and biodiesel in Figure 4 for diesel cars as such. However, due to the trade-off between these latter emission factor differences and the total emissions calculated in the baseline scenario, the maximum absolute emission savings are reached already in 2016 (57 tons) and by 2030 the annual emission savings have reduced to 22 tons.




Figure 10 TSP emissions for diesel cars and NO<sub>x</sub> emissions for gasoline cars for the baseline and BS2 scenarios, 65 \$ mileage forecast

For gasoline cars, the NO<sub>x</sub> emissions are shown in Figure 10 for the baseline scenario and BS2. The emissions decrease significantly throughout the forecast period due to gradually lower NO<sub>x</sub> emission factors (Figure 5), and total mileage reductions until 2020 (Figure 1). Being based on the emission factor differences in Figure 5, the relative emission differences between neat gasoline and the use of E5 and E85 is expected to be small. The largest emission penalty is calculated for 2010 (537 tons), and the smallest emission penalty reaches 68 tons in 2030.

The summary Table 3 shows the percentage differences between baseline and biofuel scenario 1 and 2 for fuel consumption and emissions calculated in REBECA.

Table 3 - Fuel consumption and emission percentage differences between baseline and biofuel scenario 1 and 2

| Year | Mileage forecast: 65 \$ |                 |     |      |                 |          |                     |                  |                   |      | Mileage forecast: 100 \$ |                 |      |     |                 |          |                     |                  |                   |
|------|-------------------------|-----------------|-----|------|-----------------|----------|---------------------|------------------|-------------------|------|--------------------------|-----------------|------|-----|-----------------|----------|---------------------|------------------|-------------------|
|      | En                      | NO <sub>x</sub> | VOC | CO   | CO <sub>2</sub> | TSP Exh. | TSP Exh. + Non exh. | PM <sub>10</sub> | PM <sub>2.5</sub> |      | En                       | NO <sub>x</sub> | VOC  | CO  | CO <sub>2</sub> | TSP Exh. | TSP Exh. + Non exh. | PM <sub>10</sub> | PM <sub>2.5</sub> |
| BS1  | 2010                    | -0.2            | 1.5 | -2.5 | 0.4             | -5.9     | -3.6                | -1.6             | -2.0              | -2.5 | -0.2                     | 1.5             | -2.4 | 0.4 | -5.9            | -3.6     | -1.6                | -2.0             | -2.5              |
|      | 2015                    | -0.3            | 1.5 | -1.5 | 0.7             | -8.2     | -4.8                | -1.5             | -2.0              | -2.8 | -0.3                     | 1.5             | -1.5 | 0.6 | -8.2            | -4.8     | -1.5                | -2.0             | -2.8              |
|      | 2020                    | -0.4            | 1.7 | -0.5 | 1.3             | -10.4    | -5.9                | -1.2             | -1.7              | -2.5 | -0.4                     | 1.7             | -0.5 | 1.2 | -10.4           | -5.9     | -1.2                | -1.7             | -2.5              |
|      | 2025                    | -0.4            | 1.7 | 0.2  | 1.7             | -10.4    | -5.6                | -0.6             | -0.9              | -1.5 | -0.4                     | 1.7             | 0.2  | 1.7 | -10.4           | -5.5     | -0.6                | -0.9             | -1.5              |
|      | 2030                    | -0.4            | 1.5 | 0.4  | 2.0             | -10.4    | -5.1                | -0.4             | -0.6              | -0.9 | -0.4                     | 1.5             | 0.4  | 1.9 | -10.4           | -5.0     | -0.4                | -0.6             | -0.9              |
| BS2  | 2010                    | -0.2            | 1.5 | -2.5 | 0.4             | -5.9     | -3.6                | -1.6             | -2.0              | -2.5 | -0.2                     | 1.5             | -2.4 | 0.4 | -5.9            | -3.6     | -1.6                | -2.0             | -2.5              |
|      | 2015                    | -0.4            | 1.9 | -1.5 | 0.9             | -10.9    | -6.5                | -2.1             | -2.7              | -3.7 | -0.4                     | 1.9             | -1.5 | 0.8 | -10.9           | -6.4     | -2.1                | -2.7             | -3.7              |
|      | 2020                    | -0.7            | 2.4 | 0.0  | 2.0             | -15.9    | -9.0                | -1.8             | -2.6              | -3.8 | -0.7                     | 2.4             | 0.0  | 1.9 | -15.9           | -9.0     | -1.8                | -2.6             | -3.8              |
|      | 2025                    | -0.9            | 2.9 | 1.8  | 3.6             | -20.9    | -11.0               | -1.3             | -1.9              | -3.0 | -0.9                     | 3.0             | 1.6  | 3.5 | -20.9           | -10.9    | -1.3                | -1.9             | -3.0              |
|      | 2030                    | -1.1            | 2.8 | 3.3  | 5.2             | -25.8    | -12.2               | -0.9             | -1.3              | -2.2 | -1.1                     | 2.8             | 3.1  | 5.0 | -25.8           | -12.0    | -0.9                | -1.3             | -2.2              |

The emission consequences of using biofuel in road transport even at blend ratios up to 25 % are small. For NO<sub>x</sub> and VOC the emission deviations between the baseline and biofuel scenarios are 3 % or less. For CO and exhaust TSP the largest emission differences, 5 % and -12 %, respectively, occur between the baseline and biofuel scenario 2 in 2030, related to a biofuel share of 25 %. CO is, however, of less environmental importance, and if for TSP the emission contribution coming from non exhaust is included in a total TSP assessment, the emission differences between baseline and biofuel scenarios become considerably smaller (c.f. Section 5.2).

## 6. Summary and conclusion

With CO<sub>2</sub> as an exception, the emission consequences of using biofuel in road transport even at blend ratios up to 25 % are small. For NO<sub>x</sub> and VOC the emission variations between the baseline and biofuel scenarios are 3 % or less. For CO and exhaust TSP the largest emission differences, 5 % and -12 %, respectively, occur between the FS and BS2 scenarios in 2030. The biofuel emission impacts are insignificant for NO<sub>x</sub>, VOC, CO and TSP compared to the generally large emission reductions predicted in all scenarios driven by the gradual strengthened emission standards for new vehicles, by far outweighing the emission influence from biofuels and traffic growth.

For CO<sub>2</sub> significant emission differences are calculated between FS and the biofuel scenarios; the largest difference of 26 % occurs between FS and BS2 in 2030. The reason for these differences is that the present inventory follows the calculation approach prescribed by the UNFCCC and UNECE CLRTAP conventions. For road transport, only the vehicle based emissions are made up, and further, the biofuel part of the combusted fuel are regarded as CO<sub>2</sub> neutral. Emissions associated with e.g. biofuel production and alternative use of biomass are treated in other relevant UNFCCC/UNECE inventory categories. The focus on direct vehicle emissions for road transport as a single sector makes sense for the combustion related emissions of NO<sub>x</sub>, TSP, CO and VOC, which have important environmental impacts on local air quality and health. For CO<sub>2</sub>, however, the calculated emission differences cannot be assessed by regarding road transport alone.

Being a greenhouse gas, the emission impacts of CO<sub>2</sub> must be seen from a global warming and policy perspective. So, to answer the question if bio fuels should be introduced from a society point of view an integrated W-t-W analysis and welfare economic Cost Benefit Analysis is necessary. Such an integrated analysis describes the emission and welfare effects for the full chain of production, distribution and combustion of bio fuels, and especially all the indirect consequences of re-allocating society's scarce resources (land, real capital and labour) for bio fuel production. The most important parts of the W-t-W analysis are agricultural land use change, decreasing use of biomass for energy production and the actual production of the biofuel.

For 1. generation biodiesel and bio ethanol Slentø et al. (2010) find that even if fossil fuel is used in the production process there will still be a decrease in total CO<sub>2</sub> emissions. For 2. generation bio ethanol the total CO<sub>2</sub> emissions increase. This is due to an assumption that wheat straw which has been used for energy production has to be substituted by coal.

Slentø et. al. (2010) also analyses the welfare economic consequences of producing and consuming biodiesel and bio ethanol. The result is highly dependable on the oil price, the price of agricultural production that is lost and the shadow price of CO<sub>2</sub>. Under realistic price assumptions biodiesel and 1. generation bio ethanol is not profitable to society while 2. generation bio ethanol is. The result, however, will change if agricultural products become more expensive relative to oil.

The calculation method related to biofuel usage in road transport is well established for vehicle based CO<sub>2</sub> emissions alone and hence the estimated emissions presented in this study are regarded as very precise based on the present forecast data for fleet composition and vehicle mileage. The emission estimates for NO<sub>x</sub>, VOC, CO and TSP presented in this study are less certain than for CO<sub>2</sub> due to the relatively scarce biofuel emission data implemented in the calculations. As a consequence, the obtained emission results must be assessed with care.

Bearing in mind these uncertainties, the calculation approach for emissions from biofuel usage presented in this study can be used as a tool to carry out sensitivity analysis, environmental impact assessment studies, or for research purposes as such. The work presented in this paper may also serve as an input for policy makers dealing with the introduction of biodiesel and bio ethanol for road transport vehicle propulsion. The GIS distributed emissions of NO<sub>x</sub>, TSP, CO and VOC are further used as input for air dispersion modelling purposes, subsequently carried out in REBECa.

## Acknowledgements

The present work has been funded by the Programme Commission on Energy and Environment under the Danish Strategic Research Council.

## References

AVL MTC, 2011: Unpublished data material for emission measurements of 17 FFV's from the Swedish inspection and maintenance programme.

Delgado, R., 2003: "Comparison of vehicle emissions at European Union annual average temperatures from E0 and E5 petrol", Report LM030411, IDIADA AUTOMOTIVE TECHNOLOGY, 22 pp.

de Serves C., 2005: "Emissions from Flexible Fuel Vehicles with different ethanol blends", Report Nr. AVL MTC 5509, ISSN 1103-0240, 46 pp.

EU Directive 2009/28/EC: Directive 2009/28/EC on the promotion of the use of energy from renewable sources. Commission of the European Communities 2009. Available at: <http://eur-lex.europa.eu>.

Durbin, T.D., Cocker, D.R., Sawant, A.A, Johnson, K., Miller, J.W., Holden, B.B., Helgeson, N.L., Jack, J.A., 2007: Regulated emissions from biodiesel fuels from on/off-road applications, Atmospheric Environment 41 (2007) 5647–5658

EMEP/EEA, 2009: Air Pollutant Emission Inventory Guidebook, prepared by the UNECE/EMEP Task Force on Emissions Inventories and Projections (TFEIP). Available at <http://www.eea.europa.eu/publications/emep-eea-emission-inventory-guidebook-2009> (02-02-2010).

EPA, 2002: A Comprehensive Analysis of Biodiesel Impacts on Exhaust Emissions Draft Technical Report Environmental Protection, EPA420-P-02-001, United States Environmental Protection Agency, October 2002

Fontaras, G., Samaras, Z., Miltsios, G., 2007: Experimental Evaluation of Cottonseed Oil-Diesel Blends as Automotive Fuels via Vehicle and Engine Measurements, , SAE paper 2007-24-0126.

Fontaras, G., Tzamkiozis, T., Pistikopoulos, P., Samaras, Z., 2008: Experimental evaluation of biodiesel impact on vehicle regulated and non-regulated exhaust emissions over legislated and real world driving cycles, Transport and Air Pollution, 17th Symposium, 16th-17th June 2008.

Fosgerau et al., 2007: Langsigtet fremskrivning af vejtrafik. Indikation af fremtidige problemområder - Baggrundsrapport. Danmarks Transportforskning. Rapport 2: 50 pp (in Danish). [http://www.transport.dtu.dk/upload/institutter/dtu%20transport/pdf\\_dtf/rapporter/rapporter%202007/fremskrivning%20af%20trafikken\\_baggrund.pdf](http://www.transport.dtu.dk/upload/institutter/dtu%20transport/pdf_dtf/rapporter/rapporter%202007/fremskrivning%20af%20trafikken_baggrund.pdf).

Hoefnagels, R., Smeets, E. Faaij, A.: Greenhouse gas footprints of different biofuel production systems. Renewable and Sustainable Energy Reviews 2010; 14:1661-1694.

Hull, A., Golubkov, I., Kronberg, B., Marandzheva, T., van Stam, J., 2005: "An alternative fuel for spark ignition engines", International Journal of Engine Research, vol. 7, 203-214.

Jensen, T.C., Winther, M. 2009: Fremskrivning af vejtransportens energiforbrug til REBECa-projektet, internal research note, 16 pp.

Londo, M., Lensink, S., Wakker, A., Fischer, G., Prieler, S., van Velthuisen, H., de Wit, M., Faaij, A., Junginger, M., Berndes, G., Hansson, J., Egeskog, A., Duer, H., Lundbaek, J., Wisniewski, G., Kupczyk, A. Könighofer, K.: The REFUEL EU road map for biofuels in transport: Application of the project's tools to some short-term policy issues. *Biomass and Bioenergy* 2010; 34: 244-250.

Martini, G., Astorga, C., Farfaletti, A., 2007a: Effect of Biodiesel Fuels on Pollutant Emissions from EURO 3 LD Diesel Vehicles (1), report EUR 22745 EN, Institute for Environment and Sustainability, Joint Research Centre.

Martini G., Manfredi U., Mellios G., Mahieu V., Larsen B., Farfaletti A., Krasenbrink A., De Santi G., 2007b: "Joint EUCAR/JRC/CONCAWE study on: Effects of gasoline vapour pressure and ethanol content on evaporative emissions from modern cars", EUR 22713 EN.

Martini, G., Astorga, C., Adam, T., Farfaletti, A. Manfredi, U., Montero, L., Krasenbrink, A., Larsen, B., De Santi, G., 2009: Effect of Fuel Ethanol Content on Exhaust Emissions of a Flexible Fuel Vehicle, EUR 24011 EN – 2009, DOI 10.2788/39589, 53 pp.

McCormick, R.L., Tennant, C.J., Hayes, R.R., Black, S., Ireland, J., McDaniel, T., Williams, A., Frailey, M., Sharp, C.A., 2005: Regulated Emissions from Biodiesel Tested in Heavy-Duty Engines Meeting 2004 Emission Standards; SAE paper 2005-01-2200.

Menichetti, E., Otto, M.: Energy balance and greenhouse gas emissions of biofuel from a life-cycle perspective. In Howarth R W and Bringezu S (eds.). *Biofuels: Environmental Consequences and Interactions with Changing Land Use*. Proceedings of the Scientific Committee on Problems of the Environment (SCOPE) International Biofuels Project. Rapid Assessment, 22-25 September 2008. Gummersbach Germany. Available at <http://cip.cornell.edu/biofuels/>

Nielsen, O-K., Winther, M., Mikkelsen, M.H., Lyck, E., Nielsen, M., Hoffmann, L., Gyldenkærne, S. & Thomsen, M. 2009: Projection of Greenhouse Gas Emissions. 2007 to 2025. National Environmental Research Institute, University of Aarhus. 211 s. NERI Technical Report 703.

Pelkmans, L., Lenaers, G., Bruyninx, J., De Vlieger, I., 2010: Emissions and fuel consumption of modern flexifuel and gasoline vehicles on various ethanol blends, Transport and Air Pollution Symposium – 18<sup>th</sup> Symposium, Zürich, Schweiz, 18-19 May 2010.

Slentø, E., Møller, F., Winther, M. Mikkelsen, M.H., 2010: Samfundsøkonomisk well-to-wheelanalyse af biobrændstoffer. Scenarieregninger for rapsdiesel (RME) og 1.- og 2.-generations bioethanol. Danmarks Miljøundersøgelser, Aarhus Universitet. 130 s. – Faglig rapport fra DMU nr. 797. <http://www.dmu.dk/Pub/FR797.pdf> (in Danish).

The Danish Infrastructure Commission, 2008: The Danish Infrastructure Commission: The Danish Transport Infrastructure 2030 (Summary in English).

UNEP, 2009: United Nations Environment Programme (UNEP). Towards Sustainable production and use of resources: Assessing biofuels. (UNEP) 2009. Available at <http://www.unep.org>

Westerholm, R., Ahlvik, P., Karlsson H.L., 2008: An exhaust characterisation study based on regulated and unregulated tailpipe and evaporative emissions from bi-fuel and flexi-fuel light duty passenger cars fuelled by petrol (E5), bioethanol (E70, E85) and biogas tested at ambient temperatures of +22 °C and -7 °C, Final report, March 2008, 182 pp.

Whitaker J, Ludley K, Rowe R, Taylor G, and Howard D. Sources of variability in greenhouse gas and energy balances for biofuel production: A systematic review. *GCB Bioenergy* 2010; 2:99-112.

Winther, M. 2008: Danish emission inventories for road transport and other mobile sources. Inventories until year 2006. National Environmental Research Institute, University of Aarhus. 219 pp. – NERI Technical Report No. 686. (<http://www.dmu.dk/Pub/FR686.pdf>.)

Winther, M. 2009: Emission Differences between Petroleum based Diesel and different Biodiesel Blend Ratios for Road Transport Vehicles. Transport and Air Pollution Symposium - 3rd Environment and Transport Symposium, nr. 17, Toulouse, France, 2. june 2009 - 4. june 2009.

Winther, M., 2010, Unit transformation functions from energy to volume and general expressions of fuel consumption and emission factor functions for biofuel blends used in the REBECA project, internal research note 7 pp.

Winther, M., Møller, F., Jensen, T.C. 2012: Emission consequences of introducing bio ethanol as a fuel for gasoline cars, *Atmospheric Environment* 55 (2012) 144-153.

---